

# DEXT 2.0

## ECONOMICAL HIGH-PERFORMING HIGH BAY LUMINAIRE

### Housing

Diameter : Ø14.5" | Height : 10.25" | Weight : 17.64 lbs

### Material

Housing: High Pressure Die-Cast Aluminum

Lens: Clear Polycarbonate

### Power Input

150W, 200W, 280W | 120-277V

### Lumen Output

17,400 lm (150W), 23,200 lm (200W), 34,800 lm (280W)

### Dimming

Standard 0-10V: Dims to 10%

### Color Quality

CRI 85

### Rated Life

>100,000 Hours (L70)

### Finish



Black



White

### Color Temperature



3000K



4000K



5000K

### Optics



50°



Wide

### Mounting



Bracket



Stem  
Mount



Adjustable  
Cable

### Warranty

5 Year limited warranty

### Listing



## High Efficacy Led Luminaire For General Illumination And High Ceilings

High performance durable luminaire for high ceiling applications up to 50 ft.

Delivering exceptional light levels at high operating temperatures with a delivered lumen package range of 17,400 lm to 34,800 lm.

Outdoor, wet location listed.



# METEOR

[meteor-lighting.com](https://meteor-lighting.com)

## SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

DS2	MODEL	DEXT 2.0 SERIES		
	WATTAGE	150 150W	200 200W	280 280W
	CCT / CRI	308 3000K / CRI 85	408 4000K / CRI 85	508 5000K / CRI 85
UNV	VOLTAGE	UNV 120 – 277V		
	DIMMING	NOD Non-Dimming	STV Standard 0-10V dims to 10%	
	BEAM ANGLE	50 50°	WD Wide	
	FINISH	BLK Black	WHT White	
	MOUNTING	BRK Bracket AD10 Adjustable Cable 10ft	ST2 Stem 2ft	ST4 Stem 4ft
	ACCESSORIES	SPD <sup>1</sup> Surge Protector	WG <sup>2</sup> Wire Guard (IK10 Rating)	
	RATING	OUT <sup>3</sup> Outdoor Rating	NAT <sup>4</sup> Natatorium Rating	

[↶ CLEAR FORM](#)

<sup>1</sup> Surge protector for up to 10KV. Applicable for unstable mains or facilities using high power machineries

<sup>2</sup> Please factor in change in lumen output with WG -14%

<sup>3</sup> Outdoor Rating: Coating and wiring will be changed to high UV resistant and corrosion resistant materials for long-term operation in outdoor environments

<sup>4</sup> Natatorium Rating: Coating and sealant will be changed to high corrosion resistant materials to prevent damage from long-term exposure to chlorine vapors

## TECHNICAL DETAILS

## Electrical

- 17,400 lm (150W)
- 23,200 lm (200W)
- 34,800 lm (280W)
- Power Input: Universal (120-277V)
- Operating Temperature: -22°F~113°F
- Surge Protection: Built-in is 4KV

## LED Features

- Color Temperature: 3000K, 4000K, 5000K
- CRI 85
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

## Optics

- Precision molded high transmittance clear PC lens
- Beam Angle: 50°, WD

## Advanced Dimming

- Proprietary VX Driver™ is incorporated to all dimming options for video flicker-free lighting
- Standard 0-10V: Dims to 10%

## Housing

- Diameter: Ø14.5"
- Height: 10.25"
- Material: High Pressure Die-Cast Aluminum, PC Lens
- Weight: 17.64 lbs

## Mounting

- Bracket
- Stem 2ft or 4ft; 45° Swivel Canopy Included
- Adjustable Cable 10ft

## Warranty

- 5-year limited warranty

## Listing

- ETL Wet Location Listed
- CE
- UKCA
- UGR
- IP65
- IK10

## PERFORMANCE SUMMARY\*







Delivered Lumens (Downlight)			
CCT/WATTAGE	3000K	4000K	5000K
150W	16,500lm	16,950lm	17,400lm
200W	22,000lm	22,600lm	23,200lm
280W	33,000lm	33,900lm	34,800lm

Current Consumption		
WATTAGE / VOLT	120V	277V
150W	1.52A	0.66A
200W	2.03A	0.88A
280W	3.05A	1.32A

\*Beam Angle: 50° \*Tolerance ±8%


**PHOTOMETRICS**

Below is a typical photometric representation of the Dext 2.0 fixture. Please download IES files to ensure exact photometric value.

**50°****Wide****DIMENSIONS**

## ACCESSORIES


Wire Guard




## MOUNTING OPTIONS\*

\*Junction Box not included

Stem Mount



Adjustable Cable Mount



Bracket

