

VELA 6

HIGH PERFORMING CYLINDER WITH SHROUD & DIFFUSER OPTIONS

Housing

Diameter : Ø6.4" | Height : 13.6" | Weight : 11.2 lbs

Material

Housing : High Pressure Die-Cast Aluminum Body, PC Shroud

Power Input

50W, 75W, 100W | 120-277V

Lumen Output

5,213 lm (50W), 7,821 lm (75W), 9,906 lm (100W)

Dimming

Standard 0-10V : Dims to 10%

TRC : Line-voltage phase control, dims to 1% (120V only)

DALI : Dims to 10%

Color Quality

CRI 85

Rated Life

> 100,000 Hours (L70)

Finish



Black



White

Color Temperature



3000K



3500K



4000K

Optics



80°

Mounting



Stem
Mount



Adjustable
Cable



Surface
Mount

Warranty

5 Year limited warranty

Listing



All The Performance You Need In One Family

New high performing 6-inch aperture cylinder with lumen output of 5,213 lm – 9,906 lm.

Available in Aluminum Shrouds, Polycarbonate Shrouds, Translucent Polycarbonate Diffuser or Clear Polycarbonate Diffuser options.

Suitable for general illumination in a wide variety of project applications.



METEOR

meteor-lighting.com

SPECIFICATION

PROJECT NAME

DATE

CATALOG #

QUANTITY

The product configurator function on this page works only with the latest version of Chrome or Adobe Acrobat Reader.

VA6	MODEL	VELA 6		
	WATTAGE	50 50W	75 75W	100 100W
	CCT / CRI	308 3000K / CRI 85	358 3500K / CRI 85	408 4000K / CRI 85
UNV	VOLTAGE	UNV 120 – 277V		
	DIMMING	STV 0-10V dims to 10%	TRC ¹ Line-voltage phase control, dims to 1% (120V only)	DALI ² DALI dims to 10%
	TYPE	STD Standard Cylinder ALS22 Aluminum Shroud 22" PCS22 Polycarbonate Shroud 22"	ALS16 Aluminum Shroud 16" PCS16 Polycarbonate Shroud 16" TPD Translucent Polycarbonate Diffuser	ALS19 Aluminum Shroud 19" PCS19 Polycarbonate Shroud 19" CPD Clear Polycarbonate Diffuser
	FINISH ³	BLK Black	WHT White	
	MOUNTING	SUM Surface Mount AD10 Adjustable Cable 10ft	ST2 Stem 2ft SAD10 Sloped Adjustable Cable 10ft	ST4 Stem 4ft
	ACCESSORIES	SPD ⁴ Surge Protector EMP Remote Emergency Pack AWN ^{9,11} Lutron Athena Wireless Node Standalone Module NXC ^{10,11} NX Radio Module Canopy	CON ^{5,6} Conical Lens CT ⁸ Conduit Mount AWNC ^{9,11} Lutron Athena Wireless Node Canopy	ADB ⁷ Aluminum Diffuser Band FCS Field Cut Stem Adapter Kit NX ^{10,11} NX Radio Module Standalone Module

 **CLEAR FORM**

¹ Option is only compatible with 120V and 50W

² Option is only compatible with 75W

³ For image reference, see page 5. For special color requests, please contact your Meteor representative

⁴ Surge protector for up to 10KV. Applicable for unstable mains or facilities using high-power machineries

⁵ CON can only be paired with ALS, PCS, FRS Types

⁶ Please factor in -15% change in lumen output with CON

⁷ Diffuser band comes in the same color as the luminaire and is only available with PCS16

⁸ Option is not compatible with SUM

⁹ Option is only compatible with DALI

¹⁰ Option is only compatible with STV

¹¹ Option is not compatible with SUM

TECHNICAL DETAILS**Electrical**

- 5,213 lm (50W), 7,821 lm (75W), 9,906 lm (100W)
- Power Input : Universal (120-277V)
- Operating Temperature : -13°F~112°F
- Surge Protection : Built-in is 4KV
- Remote Emergency Pack : Philips Bodine
BSL20B2UEK55C111

LED Features

- Color Temperature : 3000K, 3500K, 4000K
- CRI ≥ 85
- Long lasting LED luminaire tested under TM21 lumen maintenance L70 @ 100,000 Hrs

Optics

- Beam Angle : 80°

Advanced Dimming

- Proprietary VX Driver™ is incorporated to all dimming options for video flicker-free lighting
- Standard 0-10V dims to 10%
- TRC : Line-voltage phase control, dims to 1% (120V only)
- DALI : Dims to 10%

Housing

- Diameter : Ø6.4"
- Material : High Pressure Die-Cast Aluminum, PC Shroud
- Height :
Standard - 13.6", Diffuser - 23.1"
Shroud 16" - 22.6"
Shroud 19" - 23.9"
Shroud 22" - 25.4"
- Weight :
Standard - 11.2 lbs, Diffuser - 12.6" lbs
Aluminum Shroud 16" - 14.1 lbs
Aluminum Shroud 19" - 17.2 lbs
Aluminum Shroud 22" - 21.2 lbs
Polycarbonate Shroud 16" - 13.2 lbs
Polycarbonate Shroud 19" - 16.3 lbs
Polycarbonate Shroud 22" - 18.3 lbs

Mounting

- Stem Mount 2ft or 4ft
- Surface Mount
- Adjustable Cable Mount 10ft
- Sloped Adjustable Cable Mount 10ft

Warranty

- 5-year limited warranty

Listing

- ETL Damp Location Listed
- FCC
- CE

PERFORMANCE SUMMARY*

STD (Standard)			
CCT/WATTAGE	3000K	3500K	4000K
50W	4,914lm	5,057lm	5,213lm
75W	7,372lm	7,586lm	7,821lm
100W	9,338lm	9,609lm	9,906lm

* Tolerance ±8%

PCS (Polycarbonate Shroud)			
CCT/WATTAGE	3000K	3500K	4000K
50W	5,587lm	5,749lm	5,927lm
75W	8,381lm	8,624lm	8,891lm
100W	10,614lm	10,923lm	11,261lm

* Tolerance ±8%

ALS (Aluminum Shroud)			
CCT/WATTAGE	3000K	3500K	4000K
50W	5,070lm	5,221lm	5,382lm
75W	7,601lm	7,827lm	8,069lm
100W	9,628lm	9,915lm	10,221lm

* Tolerance ±8%

TPD (Translucent Polycarbonate Diffuser)			
CCT/WATTAGE	3000K	3500K	4000K
50W	3,022lm	3,113lm	3,209lm
75W	4,578lm	4,717lm	4,862lm
100W	5,800lm	5,975lm	6,158lm

* Tolerance ±8%

PERFORMANCE SUMMARY*

CPD (Clear Polycarbonate Diffuser)			
CCT/WATTAGE	3000K	3500K	4000K
50W	3,864lm	3,975lm	4,085lm
75W	5,854lm	6,022lm	6,189lm
100W	7,415lm	7,628lm	7,840lm

* Tolerance $\pm 8\%$

EMP (Remote Emergency Pack)		
CCT	3000K	4000K
Lumen	1,865lm	1,980lm


* Tolerance $\pm 8\%$

Current Consumption		
WATTAGE / VOLT	120V	277V
50W	0.46A	0.20A
75W	0.68A	0.30A
100W	0.92A	0.40A


* Tolerance $\pm 8\%$

PHOTOMETRICS


Below is a typical photometric representation of the Vela 6 fixture. Please download IES files to ensure exact photometric value.




STD (STANDARD)




PCS (POLYCARBONATE SHROUD)



ALS (ALUMINUM SHROUD)



**TPD (TRANSLUCENT
POLYCARBONATE DIFFUSER)**



CPD (CLEAR POLYCARBONATE DIFFUSER)

COLOR FINISH

Black Finish



White Finish



ACCESSORIES

Polycarbonate Shroud



Aluminum Shroud



Aluminum Diffuser Band



Aluminum Shroud With Conical Lens



Clear Polycarbonate Diffuser



Translucent Polycarbonate Diffuser








VELA 6

HIGH PERFORMING CYLINDER
WITH SHROUD & DIFFUSER OPTIONS


DIMENSIONS

Standard Cylinder


Clear Polycarbonate Diffuser /
Translucent Polycarbonate DiffuserAluminum Shroud /
Polycarbonate Shroud 16"Aluminum Shroud /
Polycarbonate Shroud 19"Aluminum Shroud /
Polycarbonate Shroud 22"

DIMENSIONS


Remote Emergency Pack



Conduit Mount




Lutron Athena Wireless Node / NX Radio Standalone Module




DIMENSIONS

Lutron Athena Wireless Node Canopy




NX Radio Node Canopy




MOUNTING OPTIONS*

*Junction Box not included


Stem Mount



Adjustable Cable Mount



Sloped Adjustable
Cable Mount



Surface Mount

